

Table of Contents

Header	1
Change attribute value	1
xslt php transformation	1

Header

```
<?xml version="1.0" encoding="utf-8"?>
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
version="1.0">

</xsl>
```

Change attribute value

```
<xsl:template match="@*|node()">
  <xsl:copy>
    <xsl:apply-templates select="@*|node()"/>
  </xsl:copy>
</xsl:template>
<xsl:template match="@type[parent::property]">
  <xsl:attribute name="type">
    <xsl:value-of select="'your value here'"/>
  </xsl:attribute>
</xsl:template>
```

```
<xsl:template match="@type[parent::xhtml:property]">
  <xsl:attribute name="type">
    <xsl:text>some new value</xsl:text>
  </xsl:attribute>
</xsl:template>
```

xslt php transformation

```
<?php

// import XML
$xml = new DomDocument();
$xml->load("rss.xml");

// import XSLT
$xml = new DomDocument();
$xml->load("rss2html.xsl");

// create XSLT
$proc = new xsltprocessor();
$proc->importStylesheet($xml);

// finishing
```

```
echo $proc->transformToXML($xml);  
?>
```

From:
<https://wiki.janforman.com/> - **wiki.janforman.com**

Permanent link:
<https://wiki.janforman.com/xslt>

Last update: **2017/11/08 13:52**

