

Table of Contents

- Force reboot** 1
- Scan with NMAP** 1
- Manual IP/GW Configuration** 1
- Restart SWAP** 1
- Free cache** 1
- dd full drive** 1
- erase full drive** 1

Force reboot

```
echo 1 > /proc/sys/kernel/sysrq
echo b > /proc/sysrq-trigger
```

Scan with NMAP

```
nmap -p 1-65535 -T4 -A -P0 -v hostname/ip
```

Check vulnerabilities

```
nmap -Pn --script vuln hostname/ip
```

Manual IP/GW Configuration

```
ifconfig eth0 10.0.0.1 netmask 255.255.255.0
route add default gw 10.0.0.254
```

Restart SWAP

```
sudo /sbin/swapoff -a && sudo /sbin/swapon -a
```

Free cache

```
echo 3 > /proc/sys/vm/drop_caches
```

dd full drive

```
dd if=/dev/sdX of=/dev/sdY bs=64K conv=noerror,sync
```

erase full drive

```
dd if=/dev/zero of=/dev/sdY bs=64K conv=noerror,sync
```

From:
<https://wiki.janforman.com/> - wiki.janforman.com

Permanent link:
<https://wiki.janforman.com/linux:commands?rev=1728905230>

Last update: **2024/10/14 13:27**

