

# Table of Contents

- Active Directory Mode** ..... 1
  - Set DNS resolver* ..... 1
  - Kerberos.conf* ..... 2
  - Enable AD* ..... 2
  - WSDD* ..... 2
  - Verify* ..... 2
  - Set resolv.conf* ..... 2
  - smbstatus* ..... 3
- Check Samba Dialects** ..... 3
- Redhat Install** ..... 3
- Enable startup** ..... 3
- smb.conf** ..... 3
- Add users** ..... 4
- Samba users mapping to Linux** ..... 4
- Mount SAMBA device** ..... 4
- Mount SAMBA with older protocol** ..... 5
- Turn off securitySignature** ..... 5

# Active Directory Mode

Server 2012\_R2 (from 4.21.0) supported 100000 users and computers, 100 DC in domain tested

**Change Directory Server** ✕

Current Directory Server:  
ad.corp.janforman.com|

Change to:

Any writable Domain Controller

This Domain Controller or AD LDS instance

Name	Site	DC Type	DC Version	Status
<Type a Directory Server name[:port] here>				
ad.corp.janforman.com	Osek-HQ	GC	W2K8 R2	Online

Save this setting for the current console

**IN LXC YOU MUST USE PRIVILEGED CONTAINER AND DNS may be 127.0.0.1 in the end!**

Insert AD name ad.corp.janforman.com

```
sudo vi /etc/hostname
sudo vi /etc/hosts
```

etc/cloud.cfg

```
preserve_hostname: true
```

```
sudo apt-get install samba krb5-user krb5-config winbind smbclient libpam-winbind libnss-
winbind wsdd
```

wsdd2 conflicts with SMBD!

```
Kerberos Realm: CORP.JANFORMAN.COM
Kerberos servers for your realm: ad.corp.janforman.com
Administrative server for your Kerberos realm: ad.corp.janforman.com
```

```
sudo mv /etc/samba/smb.conf /etc/samba/smb.conf.original
sudo samba-tool domain provision --use-rfc2307 --interactive
```

## Set DNS resolver

```
sudo mkdir /etc/systemd/resolved.conf.d/
```

/etc/systemd/resolved.conf.d/custom.conf

```
[Resolve]
DNSStubListener=no
Domains=corp.janforman.com
DNS=127.0.0.1
```

sudo systemctl restart systemd-resolved  
or simply disable that service

add to smb.conf global section

```
dns forwarder = 172.24.16.254
```

## Kerberos.conf

```
[libdefaults]
    default_realm = CORP.JANFORMAN.COM
    dns_lookup_realm = false
    dns_lookup_kdc = false

[realms]
CORP.JANFORMAN.COM = {
    kdc = ad.corp.janforman.com
    admin_server = ad.corp.janforman.com
    default_domain = corp.janforman.com
}

[domain_realm]
    ad = CORP.JANFORMAN.COM
```

## Enable AD

```
sudo mv /etc/krb5.conf /etc/krb5.conf.original
sudo cp /var/lib/samba/private/krb5.conf /etc/
sudo systemctl disable --now smbd nmbd winbind
sudo systemctl unmask samba-ad-dc
sudo systemctl enable --now samba-ad-dc wsdd
```

## WSDD

/etc/default/wsdd

```
WSDD_PARAMS="-w CORP"
```

## Verify

```
sudo samba-tool domain level show
smbclient -L localhost -N

kinit administrator
klist
```

## Set resolv.conf

```
sudo rm -f /etc/resolv.conf && sudo vi /etc/resolv.conf
nameserver 127.0.0.1
domain corp.janforman.com
```

## smbstatus

```

Samba version 4.15.13-Ubuntu
PID      Username      Group          Machine          Protocol Version
Encryption      Signing
-----
1526     root         users         172.24.16.123 (ipv4:172.24.16.123:50210) SMB3_11
-         -            partial(AES-128-CMAC)

Service    pid    Machine      Connected at          Encryption  Signing
-----
public     1526   172.24.16.123 Wed Jun 21 09:31:07 PM 2023 UTC -          AES-128-CMAC

Locked files:
Pid      User(ID)  DenyMode  Access    R/W      Oplock      SharePath  Name
Time
-----
1526     0         DENY_NONE 0x100081  RDONLY   NONE        /mnt . Wed Jun
21 21:31:11 2023
1526     0         DENY_NONE 0x100081  RDONLY   NONE        /mnt . Wed Jun
21 21:31:11 2023
1526     0         DENY_NONE 0x100081  RDONLY   NONE        /mnt . Wed Jun
21 21:31:09 2023

```

## Check Samba Dialects

```

nmap --script smb-protocols 192.168.101.0/24
nmap -sS -sV -sC 192.168.101.0/24
nmap --script=smb-os-discovery

```

## Redhat Install

```

yum install samba samba-client samba-common

```

## Enable startup

```

systemctl enable smb.service
systemctl enable nmb.service
systemctl restart smb.service
systemctl restart nmb.service

```

## smb.conf

```

[global]
workgroup = WINDOWS
server string = Samba Server Version %v
netbios name = SAMBA
log level = 1

```

```
log file = /var/log/samba/log.%m
max log size = 50
security = user
local master = no
os level = 33
preferred master = no
wins support = no
#===== connect to existing wins or enable wins support
wins server = 172.24.16.254
wins proxy = yes
#=====
dns proxy = yes
map to guest = bad user

username map = /etc/samba/smbusers

use sendfile = 1
deadtime = 10

load printers = no
printing = bsd
printcap name = /dev/null
disable spoolss = yes

#===== Share Definitions
[public]
comment = Public
path = /storage/public
public = yes
writable = yes
printable = no
guest ok = yes
```

## Add users

```
smbpasswd -a <linuxuser>
```

## Samba users mapping to Linux

```
/etc/samba/smbusers
```

```
linuxuser = sambaname
```

## Mount SAMBA device

```
/etc/fstab
```

```
//172.24.16.20/backup_oracle /backup_oracle cifs
_netdev,rw,username=USER,password=PASSWORD,file_mode=0640,dir_mode=0750,uid=oracle,gid=oinsta
ll 0 0
```

# Mount SAMBA with older protocol

```
mount -o vers=1.0 //x.x.x.x/share /mnt/samba
```

## Turn off securitySignature

Tuning speed

```
reg add "HKLM\SYSTEM\CurrentControlSet\Services\LanmanWorkstation\Parameters" /v  
RequireSecuritySignature /t REG_DWORD /d 0 /f  
reg add "HKLM\SYSTEM\CurrentControlSet\Services\LanManServer\Parameters" /v  
RequireSecuritySignature /t REG_DWORD /d 0 /f
```

From:

<https://wiki.janforman.com/> - **wiki.janforman.com**

Permanent link:

<https://wiki.janforman.com/linux:samba>

Last update: **2025/05/20 11:08**

