

Table of Contents

- LXC Images** 1
- LXC in Proxmox** 1
- Restore unmanaged LXC container** 1
- Mount LXC container for maintenance** 1
- Share DELL Compact Flash** 1
- Transfer files to LXC** 1
- Service cannot start** 1
- Low security better IO** 2
- Move LXC from loopback to filesystem** 2
- LXC Container information** 2
- inittab** 2
- Custom LXC Stop** 2

LXC Images

<https://images.linuxcontainers.org/images/>

LXC in Proxmox

/usr/share/perl5/PVE/LXC/Setup

Restore unmanaged LXC container

working with any linux distro
cmode shell (no login)

```
pct restore 100 vzdump-opensuse-100-xxx.tar.gz -storage=local-lvm -ostype=unmanaged -cmode shell
```

Mount LXC container for maintenance

```
pct mount CTID
```

to mount a container's volumes to /var/lib/lxc/CTID/rootfs/

Share DELL Compact Flash

/etc/pve/lxc/xxx.conf

```
mp0: /mnt/cflash,mp=/mnt
```

Transfer files to LXC

“pct pull” and “pct push” to transfer files from and to running containers
“pct exec” and “pct enter” to run individual commands or to spawn a shell inside a running container

Service cannot start

Systemd related - remove this line

```
PrivateTmp=true
```

Background services from command line terminated after start (rc.local for example)

```
options disable /dev/console
```

Low security better IO

```
pct restore CTID backup.tar.gz --rootfs local:0
```

This is identical to “simfs” in OpenVZ but unsecured.

```
/dev/X /c ext4 defaults,noatime,nodiratime,nobh,commit=40,barrier=0,data=writeback 0 2
```

```
/usr/share/perl5/PVE/LXC.pm
```

Turn off ACL

```
/var/lib/lxc/100/config
```

```
lxc.rootfs.options = noatime
```

Move LXC from loopback to filesystem

```
sudo vzdump 100 -compress lzo -dumpdir /var/lib/vz/dump -mode snapshot -remove 0  
sudo pct restore 100 /var/lib/vz/dump/vzdump-lxc-101-xxx.tar.lzo --rootfs local:0
```

LXC Container information

```
lxc-info -n ID
```

```
Name:          105  
State:         RUNNING  
PID:          2744  
IP:           10.160.149.27  
CPU use:      291440.41 seconds  
Memory use:   5.01 GiB  
KMem use:     0 bytes  
Link:         veth105i0  
TX bytes:     179.15 GiB  
RX bytes:     109.61 GiB  
Total bytes:  288.76 GiB
```

inittab

```
pf:12345:powerwait:/sbin/halt
```

Custom LXC Stop

lxc.signal.stop value in your container's config. For example, SIGKILL

From:
<https://wiki.janforman.com/> - **wiki.janforman.com**

Permanent link:
<https://wiki.janforman.com/lxc>

Last update: **2023/05/03 22:54**

