

# Table of Contents

RSYNC .....

/etc/rsyncd.conf .....

/etc/rsyncd.secrets .....

Synchronize with dir .....

1

1

1

1

# RSYNC

## /etc/rsyncd.conf

```
use chroot = yes

[documents]
    path = /storage/public
    comment = Public
    uid = nobody
    gid = nobody
    read only = no
    list = yes
    auth users = rsyncclient
    secrets file = /etc/rsyncd.secrets
    hosts allow = 10.0.0.0/255.0.0.0
```

## /etc/rsyncd.secrets

```
rsyncclient:passWord
backup:Password
user:password
```

```
sudo chmod 600 /etc/rsyncd.secrets
```

## Synchronize with dir

```
rsync -avzhe ssh --delete /opt/arcgis/server/usr/directories/
root@10.160.149.26:/opt/arcgis/server/usr/directories
```

-bwlimit=100 - limit transferring speed to 100 kB/s  
-delete - delete files that are not in source directory  
-remove-source-files - delete file after transfer (a.k.a moving files :)  
-sparse - handle sparse files efficiently

From:  
<https://wiki.janforman.com/> - **wiki.janforman.com**

Permanent link:  
<https://wiki.janforman.com/rsync>

Last update: **2023/02/23 11:25**

