

## Table of Contents

<b>Header</b> .....	1
<b>Change atribute value</b> .....	1
<b>xslt php transformation</b> .....	1

# Header

```
<?xml version="1.0" encoding="utf-8"?>
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="1.0">

</xsl>
```

## Change attribute value

```
<xsl:template match="@*|node()">
  <xsl:copy>
    <xsl:apply-templates select="@*|node()"/>
  </xsl:copy>
</xsl:template>
<xsl:template match="@type[parent::property]">
  <xsl:attribute name="type">
    <xsl:value-of select="'your value here'"/>
  </xsl:attribute>
</xsl:template>
```

```
<xsl:template match="@type[parent::xhtml:property]">
  <xsl:attribute name="type">
    <xsl:text>some new value</xsl:text>
  </xsl:attribute>
</xsl:template>
```

## xslt php transformation

```
<?php

// import XML
$xml = new DomDocument();
$xml->load("rss.xml");

// import XSLT
$xml = new DomDocument();
$xml->load("rss2html.xsl");

// create XSLT
$proc = new xsltprocessor();
$proc->importStylesheet($xml);

// finishing
echo $proc->transformToXML($xml);
?>
```

From:  
<https://wiki.janforman.com/> - [wiki.janforman.com](https://wiki.janforman.com/)

Permanent link:  
<https://wiki.janforman.com/xslt>

Last update: **2017/11/08 13:52**

